

## Material Safety Data Sheet for

### C18650CC 2.6Ah Cylindrical Lithium-Ion Cell

#### Section 1 Chemical Product and Company Identification

**Product information:**

Trade name: C18650CC Lithium-Ion Cell

Model: 18650 2.6Ah

Nominal voltage: 3.7V

Rated capacity: 2600mAh

Lithium-equivalent content: 0.65g

**Manufacture information:**

Manufacturer: Shenzhen BAK Battery Co., Ltd.

Address: BAK Industrial Park, Kuichong Street, Longgang District,  
 Shenzhen, Guangdong, China

Telephone: +86-755-89770161

#### Section 2 Composition/Information on Ingredients

Chemical Name	Molecular Formula	CAS No.	Weight Percentage/% (approximate)
Lithium cobalt oxide	LiCoO <sub>2</sub>	12190-79-3	37
Carbon ( such as graphite )	C	7440-44-0	16
Aluminum	Al	7429-90-5	4
Copper	Cu	7440-50-8	7
Steel	Fe	7439-89-6	18
lithium hexafluorophosphate	LiPF <sub>6</sub>	21324-40-3	1
Organic carbonates	—	—	9
Plastic	—	—	6
Nickel, PVDF, others	—	—	2

#### Section 3 Hazards Identification

The lithium ion cells are not hazardous when used according to the instructions of manufacturer under normal conditions. In the case of abuse, there is a risk of rupture, fire, heat, leakage of internal components, which could cause a casualty loss. Abuses include but are not limited to the following: Overcharge, short circuit, expose to fire, hammering, crushing, puncturing, crushing,

and disassembly.

## **Section 4 First-Aid Measures**

The lithium cells are not hazardous with eye and skin contact under normal circumstance. In case of fire or rupture, the leakage of internal hazardous substance and formation of hazardous substances could occur. Take the following measures:

Eyes: Check for and remove any contact lenses. Immediately flush with plenty of clean water for at least 15 minutes, seek medical assistance.

Skin: Immediately flush with plenty of clean water for 15 minutes; seek medical assistance if severe.

Inhalation: If inhaled, remove to fresh air immediately, seek medical assistance, and ventilate the contaminated area.

Ingestion: Rinse mouth with clean water immediately, activate vomit under supervised assistance, and seek medical assistance.

## **Section 5 Fire-Fighting Measures**

Extinguish with plenty of water, dry powder extinguishers, sands, earth. Combustion products and decomposed products by contact of water or air with internal substance include: carbon monoxide, carbon dioxide, hydrogen fluoride, phosphorus fluoride.

## **Section 6 Accidental Release Measures**

When leakage of cells happens, liquid could be absorbed with sand, earth or an other inert substance, and the contaminated area should be ventilated.

## **Section 7 Handling and Storage**

Don't handle and store cells in contact with conductive surfaces such as bare metal work surfaces and shelving. Store and use far away from heat, sparks, open flame, or any other ignition source. Store at room temperature (<30°C) in a ventilated and dehumidified environment.

## **Section 8 Exposure Controls/Personal Protection**

There is no need for protect under normal conditions. Ventilation equipment should be installed. Gas mask and gloves should be worn when there is evidence of chemical erosion and an exposure suit is required when dealing with fire and leakage.

## **Section 9 Physical and Chemical Properties**

Cells are not a single chemical material; there are no specific physical and chemical properties such as melting point and boiling point.

Main purpose of lithium cells: Power source used in portable and digital products.

## **Section 10 Stability and Reactivity**

Cells are safe under normal conditions. The following substances might appear after catching fire or leakage: organic carbonate, hydrogen fluoride, carbon monoxide, carbon dioxide, phosphorus fluoride.

## **Section 11 Toxicological Information**

File No./Rev.:MSDS-061B

Cells are not hazardous when used properly. If the cells catch fire or the internal substance leaks, combustion products and decomposition products might have irritation and toxicity to skin, eye and respiratory systems. Toxicity data of some substance are listed following:

Hydrogen fluoride:

Extremely toxic, may be fatal if inhaled or ingested. Readily absorbed through the skin contact may be fatal. Possible being mutagen. LCLO: 50 ppm/30m (human beings), LC50 : 1276 ppm/1h

( rats).

Carbon and graphite:

Slightly hazards in case of skin contact (irritant), ingestion, inhalation, which will cause chronic damage to upper respiratory tract and cardiovascular system.

Copper:

Dust may cause respiratory irritation.

LD50: 3.5 mg kg<sup>-1</sup>(mouse).

Aluminum:

There is no hazard.

Steel:

Dust may be harmful to respiratory system.

LD50:30mg/kg ( rat ) .

## Section 12 Ecological Information

There is no influence to ecology and environment when used properly.

## Section 13 Disposal

Unwanted cells should not be treated as ordinary trash. Recycle batteries under the requirements of your governance unit. Do not throw cells into fire or expose to high temperatures. Do not disassemble, pierce, crush or similar forms of abuse. The packaging materials which contain cells can be treated as ordinary refuse.

## Section 14 Transport Information

For the international transport of lithium batteries, they must comply with these regulations: the International Maritime Dangerous Goods (IMDG) Code by International Maritime Organization (IMO), Dangerous Goods Regulations (DGR) by International Air Transport Association (IATA) and Technical Instructions for the Safe Transport of Dangerous Goods by Air (TI) by International Civil Aviation Organization (ICAO). These regulations are based on the UN Recommendations on the Transportation of Dangerous Goods, Manual of Tests and Criteria.

Lithium batteries which meet the requirements of UN38.3 (UN Manual of Tests and Criteria, Part III, subsection 38.3) could be transported by air and by sea as ordinary goods. Otherwise, cells should be transported according to Class 9, Packing Group II hazardous goods.

As the published in the UN Recommendations on the Transportation of Dangerous Goods, 15<sup>th</sup> Edition (2007), all these regulations have added some new contents to regulate the transport of lithium ion batteries. And they should be complied since 1 January 2009.

1. For lithium ion batteries, UN ID number is 3480. For lithium ion batteries contained in equipment or lithium ion batteries packed with equipment, UN ID number is 3481.
2. The consignment should be fully described by proper shipping name and packed, marked and in proper condition for carriage by air. The consignment is not classified as dangerous under the current edition of the IATA 50<sup>th</sup> Effective, Dangerous goods regulation and all applicable carrier and government regulations.
3. For transported by air, Lithium-ion Cells/Batteries shipped as “Not Restricted” Cargo: Must comply with Part 1 of P1965-P1967 accordingly; For cells, the Watt-hour rating should not be more than 20Wh; For batteries, the Watt-hour rating should not be more than 100Wh. Watt-hour rating must be marked on the outside of the battery case (marked by manufacturer). (Except those that were manufactured before 1 January 2009, which may be transported without this marking until 31 December 2010).
4. Each consignment must be accompanied with a document such as an air waybill with an indication. For those Lithium ion cells/ batteries contained in equipment, the equipment must be equipped with an effective means of preventing accidental activation.
5. Quantity per package shall not exceed 10kg.
6. Each package must be capable of withstanding a 1m drop test in any orientation without damage of cells or batteries contained therein.
7. Lithium batteries which meet the requirements of A154 could be transported by air, and the batteries manufactured by BAK meet these requirements.( A154 Lithium batteries identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport. )
8. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to short circuit.

## **Section 15 Regulatory Information**

There is no regulation on lithium batteries management.

## **Section 16 Other Information**

This information is not applied to all the cells manufactured by BAK. This information comes from reliable sources, but no warranty is made to the completeness and accuracy of information contained. BAK does not assume responsibility for any damage or loss because of misuse of cells. agrees that it is its sole responsibility to determine suitability of the products described for the its purpose and to take precautions for protection against any hazards attendant to the handling and use of the products.

Prepared/Date: December 19, 2009

Audited/Date: December 23, 2009

Approved/Date: December 24, 2009